



KINOTEHNIK Practilite 802 Litepanels Astra 6X Velvet Power 1 Bi-Color Rainproof Outsight Creamsource Micro+ Bender Essential Kit Aputure Light Storm LS1 Aputure Amran Tri-8

Light Fixture	Hind	950.00 €	1,012.16 €	1,635.00 €	1,939.70 €	789.00 €	549.90 €
	Valguskiire nurk	30°	46°	30°	13°	45°	45°
	Värvi temp.	3000-6000K	3200-5600K	2700-6500K	2700-6500K	3200-5500K	2300-6800K
	Color Accuracy Standard	CRI 96/TLCI 97	CRI 95/TLCI 95	CRI95/TLCI95	CRI 95/TLCI 95	CRI 95/TLCI 95	CRI 95/TLCI 95
	Jahutus süsteem	Passiivne	Passiivne / Ventilator	Passiivne	Passiivne	Passiivne	Passiivne
	Dimming	0/5-100%	0-100%	0-100%	0-100%	0-100%	0-100%
	Display	On-Board LED Interface	Puudub	On-Board LED Interface	On-Board LED Interface	Puudub	On-Board LED Interface
	Korpuse materjal	Alumiinium	Alumiinium / Plastik	Alumiinium	Alumiinium	Alumiinium	Alumiinium
	Photometrics	1860 fc/20,013.6 LUX - 1m	1323 fc/14,240 LUX - 1m	1296 fc/14,000 LUX - 1m	5120 fc/55,100 LUX - 1m	697 fc / 7,500 lux - 1 m	604 fc / 6500 lux - 1.0 m
	Valgusti mõõdud	36.8 x 22.1 x 5.1 cm	45.0 x 41.4 x 13.4 cm	38.1 x 30.5 x 6.9 cm	22 x 20.7 x 10.5 cm	37.8 x 32.1 x 3.3 cm	26.1 x 19.9 x 9.3 cm
Power	Valgusti kaal	4.1 kg	3.2 kg	4.45kg	3.4kg	7.5lb / 3.4kg	4.93kg
	AC Vool	100 - 240VAC, 50/60 Hz	100 - 240VAC, 50/60 Hz	90 - 264 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz
	DC Vool	14-28VDC	13-24VDC	24-35VDC	10-32 VDC	15 VDC	15 VDC
	Maksimaalne Voolu Kasutus	90W	105W	100W	80W	60W	60W
	Akupaat	Saadaval lisavarustusena 119€ - Non-Weatherproof (Gold-Mount / V-Lock) 249€ - IP54 Weatherproof (V-Lock)	Saadaval lisavarustusena 147.59€ - Non-Weatherproof (Gold-Mount / V-Lock)	Saadaval lisavarustusena 201.11€ - Non-Weatherproof (Gold-Mount / V-Lock)	Saadaval lisavarustusena 372.47€ - Non-Weatherproof (Gold-Mount / V-Lock) 522.41€ - IP54 Weatherproof (V-Lock only)	N/A	N/A
	Distantsiit juhtimine	Bluetooth (Practilite Rakendus), DMX	Lisavarustusena - Bluetooth and DMX	DMX	DMX	Füüsiline pult	Füüsiline pult
	IP Rating	IP54 (IP65 cert. In progress)	IP20	IP54	IP65	IP20	IP65
	Flicker Free	At any frame rate	At any frame rate	1000FPS	1000FPS	N/A	N/A
	LED Eluiga	40 000 hours (LM80)	N/A	50 000 hours	50 000 hours	100 000 hours	100 000 hours
	Komplekt sisaldab	Practilite 802 Fixture Yoke 60° Diffuser (1pcs) 80° Diffuser (1pcs) Diffuser Holders (2pcs) 110-220V AC/DC Toiteplokk	Litepanels Astra 6X Fixture Yoke 24V Toiteplokk	Velvet Light 1 Fixture Yoke	Creamsource Micro+ Bender Fixture Toiteplokk Yoke 60° Diffuser	Aputure LS1 Fixture Toiteplokk	Aputure Tri-8 Fixture Pult Toiteplokk V-Lock akupaat 2x F970 Aku Softbox Kandekott