

Evoke 5C/KIT/8KIT LED Full-color Spot Light

Shipping availability: April, 2026

Consumer launch: April 15, 8PM (UTC+8) 2026



► Features

- ▶ **Innovative Nebula C8 Light Engine (combining deep red, red, amber, lime, green, cyan, blue, indigo)** to achieve 1,000K-20,000K with G/M±200 adjustment
- ▶ **Compact, lightweight, and easy to use and carry**
 - Weighs only 160g/0.353lb
 - Size: 56×44×45mm/2.2×1.73×1.77"
- ▶ **Built-in battery for long runtime:** up to 2 hr 36 min, 50 min at full output
- ▶ **IP67** rating for robust underwater protection
 - Up to 30 min runtime at 1 m
 - Up to 45 min runtime at 30 m with Underwater Housing
- ▶ **3 power options**
 - Charge via the USB-C port
 - Charge using an adapter or power bank (5V/2A or higher)
 - Charge via the electronic contacts, compatible with Battery Grip, Magnetic E27 Socket Adapter, 8 kit case, and Magnetic Motorized Yoke
- ▶ **6 lighting modes:** CCT, HSI, RGBW, XY Coordinates, Gel and Effect
- ▶ **5 control methods:** On-board, NANLINK APP, CRMX, DMX/RDM and NFC
- ▶ **Modifier recognition function:** Evoke 5C recognizes modifiers with electronic contacts.
- ▶ **Magnetic design on both ends and a 1/4"-20 mount with a anti-twist design,** compatible with an extensive accessory ecosystem.
- ▶ **Evoke 5C KIT:** Carrying bag with carabiner for direct belt attachment.
- ▶ **Evoke 5C 8KIT:**

For professional production, the Evoke 5C is available in an 8-light kit, including a range of lighting and power accessories. The Evoke 5C 8KIT case built on the GUTEK T-230 protective case provides an all-in-one solution for efficient storage, protection, and charging.

 - Electronic contacts support charging of 8 fixtures and 4 battery grips.
 - 3 power options: AC power, D-tap power and PD power
 - Custom foam for organized and efficient storage of accessories.
 - GUTEK T-230 protector case with IP67 rating offers full protection, resistance to pressure and shock, and flame retardant construction.

► Target Market

- ▶ Miniature and product photography
- ▶ Large-scale professional production
- ▶ Content Creator
- ▶ Underwater production
- ▶ Theaters and museums

► What's in the Box

① Standard Kit

Evoke 5C × 1
USB-C Cable × 1
AS-MD-EV5C Magnetic Diffuser × 1
YK-EV5C Magnetic Yoke × 1
AS-MTS-EV5C Magnetic Thermal Shield × 1
User Manual × 1
Carrying Bag × 1



② **Evoke 5C KIT**

Evoke 5C × 1
USB-C Cable × 1
Magnetic Fresnel Lens × 1
Magnetic Battery Grip × 1
Magnetic Thermal Shield × 1
Magnetic Diffuser × 1
Magnetic Soft Dome × 1
Magnetic Barndoor × 1
Magnetic Snoot × 1
User Manual × 1
Carrying Bag × 1



③ **Evoke 5C 8KIT**

Evoke 5C × 8
AS-MD-EV5C Magnetic Diffuser × 8
AS-MSD-EV5C Magnetic Soft Dome × 4
WS-MCR-EV5C Magnetic CRMX Module × 8
AS-MTS-EV5C Magnetic Thermal Shield × 8
BD-EV5C Magnetic Barndoor × 4
AS-MS-EV5C Magnetic Snoot × 4
FL-5 Magnetic Fresnel Lens × 4
BT-BG-EV5C Magnetic Battery Grip × 4
5/8" Baby Pin with 1/4"-20 Thread × 4
AS-MSA-E27-EV5C Magnetic E27 Socket Adapter × 4
YK-EV5C Magnetic Yoke × 4
PJ-EV5C-15-35 Projection Attachment 15°-35° × 2
Gobo × 8
MD-SBL-EV5C Magnetic Spot Beam Lens × 2
AC Power Cable 1.5m × 1
D-tap Cable × 1
User Manual × 1
GUTEK T-230 Protector Case × 1 (Black)



④ **AS-MD-EV5C-KIT**

BD-EV5C Magnetic Barndoor × 1
AS-MS-EV5C Magnetic Snoot × 1
AS-MSD-EV5C Magnetic Soft Dome × 1

► Specification

Model	Evoke 5C	Evoke 5C 8KIT
EAN Code	6949987492504 (Standard Kit)	6949987492788
	6949987492511 (Evoke 5C KIT)	
Rated Power	6W	180W
Input Voltage/Current	DC5V/2A	DC24V/7.5A
Beam Angle	25°	
LED Light Engine	Nebula C8 Light Engine: dRRALGCBI	
CCT	1,000K-20,000K (G/M±200)	
CRI	Average 98	
TLCI	Average 98	
TM-30 Rf	Average 96	
TM-30 Rg	Average 100	
Dimming	0%-100%, by 1% increment	
Product Size	<p>Light Fixture: 56×44×45mm/2.2×1.73×1.77" USB-C Cable: 1m/39.37" AS-MD-EV5C Magnetic Diffuser: 44×44×11mm/1.73×1.73×0.433" YK-EV5C Magnetic Yoke: 67×42×69mm/2.64×1.65×2.72" AS-MTS-EV5C Magnetic Thermal Shield: 48×48×31mm/1.89×1.89×1.22" Standard Kit Carrying Bag: 135×50×75mm/5.31×1.97×2.95" Evoke 5C KIT Carrying Bag: 190×60×100mm/7.48×2.36×3.94"</p>	<p>Light Fixture: 56×44×45mm/2.2×1.73×1.77" AS-MD-EV5C Magnetic Diffuser: 44×44×11mm/1.73×1.73×0.433" AS-MSD-EV5C Magnetic Soft Dome: 44×44×31mm/1.73×1.73×1.22" WS-MCR-EV5C Magnetic CRMX Module: 52.29×43.6×20.31mm/2.06×1.72×0.8" AS-MTS-EV5C Magnetic Thermal Shield: 48×48×31mm/1.89×1.89×1.22" BD-EV5C Magnetic Barndoor: 58×60×24mm/2.28×2.36×0.95" AS-MS-EV5C Magnetic Snoot: 44×44×73.6mm/1.73×1.73×2.9" FL-5 Magnetic Fresnel Lens: Φ48.15×31.9mm/Φ1.9×1.26" BT-BG-EV5C Magnetic Battery Grip: 114×52.3×43.6mm/4.49×2.06×1.72" 5/8" Baby Pin with 1/4"-20 Thread: Φ16×107mm/Φ0.63×4.21" AS-MSA-E27-EV5C Magnetic E27 Socket Adapter: 52.29×43.6×41.36mm/2.06×1.72×1.63" YK-EV5C Magnetic Yoke: 67×42×69mm/2.64×1.65×2.72" PJ-EV5C-15-35 Projection Attachment: 171.3×93.6×93.6mm/6.74×3.69×3.69" MD-SBL-EV5C Magnetic Spot Beam Lens: Φ55.96×74.9mm/Φ2.2×2.95" Gobo/pc: 53.85×24×0.2mm/2.12×0.95×0.0079" GUTEK T-230 Protector Case: 450×375×196mm/17.72×14.76×7.72"</p>
Product Weight	<p>Light Fixture: 160g/0.353lb USB-C Cable: 28g/0.0617lb AS-MD-EV5C Magnetic Diffuser: 8g/0.0176lb YK-EV5C Magnetic Yoke: 62g/0.137lb AS-MTS-EV5C Magnetic Thermal Shield: 9g/0.0198lb Standard Kit Carrying Bag: 76g/0.168lb Evoke 5C KIT Carrying Bag: 168.2g/0.371lb</p>	<p>Light Fixture: 0.16kg/0.353LB AS-MD-EV5C Magnetic Diffuser: 0.008kg/0.0176lb AS-MSD-EV5C Magnetic Soft Dome: 0.011kg/0.024lb WS-MCR-EV5C Magnetic CRMX Module: 0.05kg/0.11lb AS-MTS-EV5C Magnetic Thermal Shield: 0.009kg/0.02lb BD-EV5C Magnetic Barndoor: 0.027kg/0.06lb AS-MS-EV5C Magnetic Snoot: 0.014kg/0.031lb FL-5 Magnetic Fresnel Lens: 0.03kg/0.066lb BT-BG-EV5C Magnetic Battery Grip: 0.18kg/0.397lb 5/8" Baby Pin with 1/4"-20 Thread: 0.05kg/0.11lb AS-MSA-E27-EV5C Magnetic E27 Socket Adapter: 0.05kg/0.11lb YK-EV5C Magnetic Yoke: 0.062kg/0.137lb PJ-EV5C-15-35 Projection Attachment: 0.15kg/0.331lb Gobo/pc: 0.00142kg/0.00313lb MD-SBL-EV5C Magnetic Spot Beam Lens: 0.075kg/0.165lb D-tap Cable: 0.06kg/0.132lb GUTEK T-230 Protector Case: 5.14kg/11.33lb</p>
Master Carton Size	<p>Standard Kit: 455×365×370mm/17.91×14.37×14.57" Evoke 5C KIT: 435×435×355mm/17.13×17.13×13.98" AS-MD-EV5C-KIT: 370×320×340mm/14.57×12.6×13.39"</p>	650×490×415mm/25.59×19.29×16.34"
Packing Quantity	<p>Standard Kit: 60 Evoke 5C KIT: 30 AS-MD-EV5C-KIT: 150</p>	3

► Accessories (Optional)

Modifiers

Picture				
Product	AS-MSD-EV5C Evoke 5C Magnetic Soft Dome	AS-MD-EV5C Evoke 5C Magnetic Diffuser	FL-5 Evoke 5C Magnetic Fresnel Lens (25°-35°)	MD-SBL-EV5C Evoke 5C Magnetic Spot Beam Lens (8°)
Picture				
Product	AS-MS-EV5C Evoke 5C Magnetic Snoot	PJ-EV5C-15-35 Evoke 5C Projection Attachment 15°-35°	BD-EV5C Evoke 5C Magnetic Barndoor	

Power

Picture		
Product	AS-MSA-E27-EV5C Evoke 5C Magnetic E27 Socket Adapter	BT-BG-EV5C Evoke 5C Magnetic Battery Grip (7.2V/3100mAh)

Control

Picture	
Product	WS-MCR-EV5C Evoke 5C Magnetic CRMX Module

Mounting

Picture		
Product	YK-EV5C Evoke 5C Magnetic Yoke	5/8" Baby Pin with 1/4"-20 Thread

Others

Picture		
Product	AS-MTS-EV5C Evoke 5C Magnetic Thermal Shield	AS-UH-EV5C Evoke 5C Underwater Housing (IP68-rated for underwater use up to 30m)



► **illumination**

	Light Only			With Evoke 5C Magnetic Fresnel Lens (25°)			With Evoke 5C Magnetic Fresnel Lens (35°)		
Distance	0.3M	0.5M	1M	0.3M	0.5M	1M	0.3M	0.5M	1M
2700K	4950 lux 460 fc	1660 lux 154 fc	404 lux 38 fc	11340 lux 1054 fc	3270 lux 304 fc	678 lux 63 fc	6320 lux 587 fc	2076 lux 193 fc	470 lux 44 fc
3200K	5480 lux 509 fc	1835 lux 170 fc	448 lux 42 fc	12570 lux 1168 fc	3630 lux 337 fc	750 lux 70 fc	7010 lux 651 fc	2296 lux 213 fc	518 lux 48 fc
5600K	5970 lux 555 fc	2026 lux 188 fc	496 lux 46 fc	13830 lux 1285 fc	4020 lux 374 fc	830 lux 77 fc	7860 lux 730 fc	2533 lux 235 fc	580 lux 54 fc
6500K	6190 lux 575 fc	2089 lux 194 fc	511 lux 47 fc	14360 lux 1334 fc	4160 lux 387 fc	856 lux 80 fc	8130 lux 755 fc	2629 lux 244 fc	597 lux 56 fc
R	929 lux 86 fc	308 lux 29 fc	73 lux 3 fc	2120 lux 197 fc	595 lux 55 fc	123 lux 11 fc	1170 lux 109 fc	385 lux 36 fc	86 lux 8 fc
G	8080 lux 751 fc	2755 lux 256 fc	671 lux 62 fc	18800 lux 1747 fc	5390 lux 501 fc	1127 lux 105 fc	10410 lux 967 fc	3450 lux 321 fc	796 lux 74 fc
B	1174 lux 109 fc	404 lux 38 fc	99 lux 9 fc	2720 lux 253 fc	779 lux 72 fc	164 lux 15 fc	1511 lux 140 fc	505 lux 47 fc	114 lux 11 fc
	With Evoke 5C Magnetic Spot Beam Lens			With Evoke 5C Projection Attachment 15°-35° (15°)			With Evoke 5C Projection Attachment 15°-35° (35°)		
Distance	0.5M	1M	2M	0.5M	1M	2M	0.5M	1M	2M
2700K	8760 lux 814 fc	2305 lux 214 fc	554 lux 52 fc	2772 lux 258 fc	593 lux 55 fc	143 lux 13 fc	1044 lux 97 fc	188 lux 18 fc	40 lux 4 fc
3200K	9710 lux 902 fc	2548 lux 237 fc	604 lux 56 fc	3050 lux 283 fc	656 lux 61 fc	157 lux 15 fc	1156 lux 107 fc	207 lux 19 fc	45 lux 4 fc
5600K	10770 lux 1001 fc	2828 lux 263 fc	677 lux 63 fc	3380 lux 314 fc	726 lux 67 fc	173 lux 16 fc	1278 lux 119 fc	229 lux 21 fc	49 lux 5 fc
6500K	11100 lux 1031 fc	2930 lux 272 fc	702 lux 65 fc	3530 lux 328 fc	753 lux 70 fc	180 lux 17 fc	1326 lux 123 fc	238 lux 22 fc	51 lux 5 fc
R	1622 lux 151 fc	416 lux 39 fc	100 lux 9 fc	515 lux 48 fc	111 lux 10 fc	26 lux 2 fc	195 lux 18 fc	35 lux 3 fc	7 lux 1 fc
G	14910 lux 1385 fc	3870 lux 360 fc	928 lux 86 fc	4610 lux 428 fc	974 lux 91 fc	234 lux 22 fc	1724 lux 160 fc	312 lux 29 fc	67 lux 6 fc
B	2176 lux 202 fc	557 lux 52 fc	132 lux 12 fc	682 lux 63 fc	145 lux 14 fc	34 lux 3 fc	255 lux 24 fc	46 lux 4 fc	9 lux 1 fc
	With Evoke 5C Magnetic Snoot			With Evoke 5C Magnetic Diffuser			With Evoke 5C Magnetic Soft Dome		
Distance	0.3M	0.5M	1M	0.3M	0.5M	1M	0.3M	0.5M	1M
2700K	863 lux 80 fc	233 lux 22 fc	50 lux 5 fc	251 lux 23 fc	80 lux 7 fc	19 lux 2 fc	199 lux 19 fc	61 lux 6 fc	14 lux 1 fc
3200K	955 lux 89 fc	261 lux 24 fc	55 lux 5 fc	277 lux 26 fc	89 lux 8 fc	21 lux 2 fc	220 lux 20 fc	67 lux 6 fc	15 lux 1 fc
5600K	1050 lux 98 fc	287 lux 27 fc	61 lux 6 fc	303 lux 28 fc	97 lux 9 fc	23 lux 2 fc	242 lux 23 fc	74 lux 7 fc	17 lux 2 fc
6500K	1094 lux 102 fc	300 lux 28 fc	64 lux 6 fc	316 lux 29 fc	101 lux 9 fc	24 lux 2 fc	251 lux 23 fc	77 lux 7 fc	17 lux 2 fc
R	163 lux 15 fc	44 lux 4 fc	9 lux 1 fc	48 lux 5 fc	15 lux 1 fc	3 lux 0.3 fc	37 lux 3 fc	11 lux 1 fc	2 lux 0.2 fc
G	1427 lux 133 fc	391 lux 36 fc	83 lux 8 fc	411 lux 38 fc	131 lux 12 fc	31 lux 3 fc	327 lux 30 fc	101 lux 9 fc	23 lux 2 fc
B	205 lux 19 fc	56 lux 5 fc	12 lux 1 fc	59 lux 6 fc	18 lux 2 fc	4 lux 0.4 fc	48 lux 5 fc	14 lux 1 fc	3 lux 0.3 fc